



700 Series

Bain marie 700

ELECTRIC BAIN-MARIE, BME7-05

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	380,00
Depth	mm	775,00	840,00
Height	mm	290,00	520,00
Weigth	Kg	21,00	27,00
Volumen	m3	0,08	0,17

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x1,5+T - 16 A
230V - III		
400V - III+N		

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC BAIN-MARIE, BME7-05

Made of stainless steel.

Tank capacity: 17 litres.

The tank is designed to accommodate GN containers.

Built with separators for containers.

Shielded elements controlled by thermostat. Pilot lights.

Thermostat temperature control (30 °C to 90 °C)


Water intake tap.

Drainage with overflow.

Power: 2800 W.

Dimensions: 350 x 775 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	312	494	0		Prever Interruptor diferencial
COLD WATER	38	494	0	1/2"	Prever llave de corte en la toma
DRAIN	38	199	0	30x25	



700 Series

Bain marie 700

ELECTRIC BAIN-MARIE, BME7-10



DIMENSIONS

		Article	Packed
Length	mm	700,00	740,00
Depth	mm	775,00	830,00
Height	mm	290,00	520,00
Weigth	Kg	34,00	40,00
Volumen	m3	0,16	0,32

ELECTRICITY

Electric power	KW	
230V -1+N		2x4+T - 32 A
230V - III		3x2,5+T - 20 A
400V - III+N		4x2,5+T - 16 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC BAIN-MARIE, BME7-10

Made of stainless steel.

Tank capacity: 30 litres.

The tank is designed to accommodate GN containers.

Built with separators for containers.

Shielded elements controlled by thermostat. Pilot lights.

Thermostat temperature control (30 °C to 90 °C)


Water intake tap.

Drainage with overflow.

Power: 6000 W

Dimensions: 700 x 775 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	662	494	0		Prever Interruptor diferencial
COLD WATER	38	494	0	1/2"	Prever llave de corte en la toma
DRAIN	38	199	0	30x25	





700 Series

Bain marie 700

GAS BAIN-MARIE, BMG7-10

DIMENSIONS

		Article	Packed
Length	mm	700,00	740,00
Depth	mm	775,00	830,00
Height	mm	290,00	520,00
Weigth	Kg	34,00	40,00
Volumen	m3	0,16	0,32

ELECTRICITY

Electric power	KW	
230V -1+N		0,05 2x2,5 - 4 A
230V - III		
400V - III+N		

WATER

Not used

GAS

Power	KW	6,40
	Kcal/h	5.504,00
LPG	Consumption (kg/h)	0,54
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,69
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS BAIN-MARIE, BMG7-10

Made of stainless steel.

Tank capacity: 30 litres.

The tank is designed to accommodate GN containers.

Built with separators for containers.

Piezoelectric ignition and pilot. Safety thermocouple.

Thermostat temperature control (30 °C to 90 °C)

Water intake tap.

Drainage with overflow.

Power: 5500 Kcal/h. (6.40 kW).

Electrical connection: 230 V - 1+N+E.

Dimensions: 700 x 775 x 290 mm.

Certificate EQNET- CE

99AR328

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	662	494			
COLD WATER	38	494	0	1/2"	Prever llave de corte en la toma
DRAIN	38	199	0	30x25	
GAS	662	494	50	R.3/4"G	Prever regulador y llave de corte individual

