



700 Series

Fryers 700

GAS FRYER, FG7-05 - 2C

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	57,00	68,00
Volumen	m3	0,23	0,35

ELECTRICITY

<u>Electric power</u>		KW	
230V - 1+N			0,05
230V - III			2x1,5+T - 2 A
400V - III+N			

WATER

Not used

GAS

Power		KW	15,00
		Kcal/h	12.900,00
LPG		Consumption (kg/h)	1,25
		Pressure (g/cm2)	37,00
Natural Gas		Consumption (m3/h)	1,59
		Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRYER, FG7-05 - 2C

Made of stainless steel

Capacity: one 15 litre oil/well.

Tank equipment: 2 small baskets 250x135 mm .

Cast iron burners.

Thermostat temperature control 60 °C to 195 °C.

Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple.

Safety thermostat.

Drainage tap.

Power: 15 kW.


Electrical connection 230 V - 1+N+T.

Dimensions: 350 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5118

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	286	540	150		Prever Interruptor diferencial
GAS	312	492	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fryers 700

ELECTRIC FRYER, FE7-05 - 2C

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	57,00	68,00
Volumen	m3	0,23	0,35

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x16+T - 80 A
230V - III		3x16+T - 40 A
400V - III+N		4x2,66+T - 25 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRYER, FE7-05 - 2C

Made of stainless steel

Capacity: one 15 litre oil/well.

Tank equipment: 2 baskets 250x135 mm by tank.

Shielded heating elements in stainless steel.

Pilot light for heating.

Control by thermostat (60 °C to 195 °C).


Safety thermostat.

Drainage tap.

Power: 12 kW.

Dimensions: 350 x 775 x 850 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	264	618	650		Prever Interruptor diferencial





700 Series

Fryers 700

ELECTRIC FRYER, FE7-05 - 1C

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	57,00	68,00
Volumen	m3	0,23	0,35

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x16+T - 80 A
230V - III		3x16+T - 40 A
400V - III+N		4x2,66+T - 25 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRYER, FE7-05 - 1C

Made of stainless steel

Capacity: one 15 litre oil/well.

Tank equipment: 1 basket 250x280 mm .

Shielded heating elements in stainless steel.

Pilot light for heating.

Control by thermostat (60 °C to 195 °C).


Safety thermostat.

Drainage tap.

Power: 12 kW.

Dimensions: 350 x 775 x 850 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	264	618	650		Prever Interruptor diferencial





700 Series

Fryers 700

GAS FRYER, FG7-10 - 4C

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	742,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	104,00	119,00
Volumen	m3	0,46	0,66

ELECTRICITY

<u>Electric power</u>		KW	
230V - 1+N			0,05
230V - III			2x1,5+T - 2 A
400V - III+N			

WATER

Not used

GAS

Power		KW	30,00
		Kcal/h	25.800,00
LPG	Consumption (kg/h)		2,50
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		3,18
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used

GAS FRYER, FG7-10 - 4C

Made of stainless steel

Capacity: two 15 litre oil/well.

Tank equipment: 2 baskets 250x135 mm by tank.

Cast iron burners.

Thermostats temperature control 60 °C to 195 °C.

Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple.

Safety thermostat.

Drainage taps.

Power: 30 kW.


Electrical connection 230 V - 1+N+T.

Dimensions: 700 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5118

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	286	540	150		Prever Interruptor diferencial
ELECTRICITY	636	540	150		Prever Interruptor diferencial
GAS	662	492	105	R.3/4"G	Prever regulador y llave de corte individual
GAS	312	492	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fryers 700

GAS FRYER, FG7-10 - 2C

DIMENSIONS

		Article	Packed
Length	mm	700,00	742,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	104,00	119,00
Volumen	m3	0,46	0,66

ELECTRICITY

Electric power	KW	
230V - 1+N		0,05
230V - III		2x1,5+T - 2 A
400V - III+N		

WATER

Not used

GAS

Power	KW	30,00
	Kcal/h	25.800,00
LPG	Consumption (kg/h)	2,50
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	3,18
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRYER, FG7-10 - 2C

Made of stainless steel

Capacity: two 15 litre oil/well.

Tank equipment: 1 basket 250x280 mm by tank.

Cast iron burners.

Thermostats temperature control 60 °C to 195 °C.

Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple.

Safety thermostat.

Drainage taps.

Power: 30 kW.


Electrical connection 230 V - 1+N+T.

Dimensions: 700 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5118

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	286	540	150		Prever Interruptor diferencial
ELECTRICITY	636	540	150		Prever Interruptor diferencial
GAS	662	492	105	R.3/4"G	Prever regulador y llave de corte individual
GAS	312	492	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fryers 700

ELECTRIC FRYER, FE7-10 - 4C

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	742,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	104,00	119,00
Volumen	m3	0,46	0,66

ELECTRICITY

<u>Electric power</u>	KW	
230V - I+N		24,00
		2x16+T - 80 A
230V - III		3x16+T - 40 A
400V - III+N		4x2,66+T - 25 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRYER, FE7-10 - 4C

Made of stainless steel

Capacity: two 15 litre oil/well.

Tank equipment: 2 baskets 250x135 mm by tank.

Shielded heating elements in stainless steel.

Pilot light for heating.

Control by thermostats (60 °C to 195 °C).


Safety thermostats.

Drainage taps.

Power: 24 kW.

Dimensions: 700 x 775 x 850 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	614	618	650		Prever Interruptor diferencial
ELECTRICITY	264	618	650		Prever Interruptor diferencial





700 Series

Fryers 700

ELECTRIC FRYER, FE7-10 - 2C

DIMENSIONS

		Article	Packed
Length	mm	700,00	742,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	104,00	119,00
Volumen	m3	0,46	0,66

ELECTRICITY

Electric power	KW	
230V -1+N		24,00
230V - III		2x16+T - 80 A
400V - III+N		3x16+T - 40 A
		4x2,66+T - 25 A

WATER

Not used

GAS

Not used

STEAM

Not used


AIR

Not used

ELECTRIC FRYER, FE7-10 - 2C

Made of stainless steel
 Capacity: two 15 litre oil/well.
 Tank equipment: 1 basket 250x280 mm by tank.
 Shielded heating elements in stainless steel.
 Pilot light for heating.
 Control by thermostats (60 °C to 195 °C).
 Safety thermostats.
 Drainage taps.
 Power: 24 kW.
 Dimensions: 700 x 775 x 850 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	614	618	650		Prever Interruptor diferencial
ELECTRICITY	264	618	650		Prever Interruptor diferencial





700 Series

Fryers 700

GAS FRYER, FG7-05 - 1C

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	57,00	68,00
Volumen	m3	0,23	0,35

ELECTRICITY

<u>Electric power</u>		KW	
230V - 1+N			0,05
230V - III			2x1,5+T - 2 A
400V - III+N			

WATER

Not used

GAS

Power		KW	15,00
		Kcal/h	12.900,00
LPG		Consumption (kg/h)	1,25
		Pressure (g/cm2)	37,00
Natural Gas		Consumption (m3/h)	1,59
		Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRYER, FG7-05 - 1C

Made of stainless steel

Capacity: one 15 litre oil/well.

Tank equipment: 1 basket 250x280 mm .

Cast iron burners.

Thermostat temperature control 60 °C to 195 °C.

Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple.

Safety thermostat.

Drainage tap.

Power: 15 kW.

Electrical connection 230 V - 1+N+T.

Dimensions: 350 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5118

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	286	540	150		Prever Interruptor diferencial
GAS	312	492	105	R.3/4"G	Prever regulador y llave de corte individual

