



700 Series

Fry-tops 700

GAS FRY-TOP, FTG7-05 VL

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	835,00
Height	mm	290,00	585,00
Weigth	Kg	43,00	55,00
Volumen	m3	0,08	0,19

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	6,30
	Kcal/h	5.418,00
LPG	Consumption (kg/h)	0,52
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,66
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG7-05 VL

Made of stainless steel.

Smooth hot-plate. Surface area: 20 dm2.

Tubular burner in stainless steel with pilot.

Safety valve and thermocouple.

Fat collector under the grill.


Power: 6.3 kW.

Dimensions: 350 x 775 x 290 mm.

Certificate EQNET- CE

99AR307

Connections points	X	Y	Z	Diameter	Information
GAS	310	494	57	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fry-tops 700

GAS FRY-TOP, FTG7-05 VR

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	835,00
Height	mm	290,00	585,00
Weigth	Kg	43,00	55,00
Volumen	m3	0,08	0,19

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	6,30
	Kcal/h	5.418,00
LPG	Consumption (kg/h)	0,52
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,66
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG7-05 VR

Made of stainless steel.

Ribbed hot-plate. Surface area: 20 dm2.

Tubular burner in stainless steel with pilot.

Safety valve and thermocouple.

Fat collector under the grill.


Power: 6.3 kW.

Dimensions: 350 x 775 x 290 mm.

Certificate EQNET- CE

99AR307

Connections points	X	Y	Z	Diameter	Information
GAS	310	494	57	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fry-tops 700

GAS FRY-TOP, FTG7-05 L

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	835,00
Height	mm	290,00	585,00
Weigth	Kg	43,00	55,00
Volumen	m3	0,08	0,19

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	6,30
	Kcal/h	5.418,00
LPG	Consumption (kg/h)	0,52
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,66
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG7-05 L

Made of stainless steel.

Smooth hot-plate.

Surface area: 20 dm2.

Tubular burner in stainless steel with pilot.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 6.3 kW.

Dimensions: 350 x 775 x 290 mm.

Certificate EQNET- CE

99AR307

Connections points	X	Y	Z	Diameter	Information
GAS	310	494	57	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fry-tops 700

GAS FRY-TOP, FTG7-05 R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	835,00
Height	mm	290,00	585,00
Weigth	Kg	43,00	55,00
Volumen	m3	0,08	0,19

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	6,30
	Kcal/h	5.418,00
LPG	Consumption (kg/h)	0,52
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,66
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG7-05 R

Made of stainless steel.

Ribbed hot-plate.

Surface area: 20 dm2.

Tubular burner in stainless steel with pilot.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 6.3 kW.

Dimensions: 350 x 775 x 290 mm.

Certificate EQNET- CE

99AR307

Connections points	X	Y	Z	Diameter	Information
GAS	310	494	57	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fry-tops 700

GAS FRY-TOP, FTG/C7-05 L

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	835,00
Height	mm	290,00	585,00
Weigth	Kg	43,00	55,00
Volumen	m3	0,08	0,19

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	6,30
	Kcal/h	5.418,00
LPG	Consumption (kg/h)	0,52
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,66
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG/C7-05 L

Made of stainless steel.

Smooth hot-plate.

50 microns thickness chromium coated steel sheeting hot-plate.

Surface area: 20 dm2.

Tubular burner in stainless steel with pilot.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 6.3 kW.

Dimensions: 350 x 775 x 290 mm.

Certificate EQNET- CE

99AR307

Connections points	X	Y	Z	Diameter	Information
GAS	310	494	57	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fry-tops 700

ELECTRIC FRY-TOP, FTE7-05 R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	835,00
Height	mm	290,00	585,00
Weigth	Kg	43,00	55,00
Volumen	m3	0,08	0,19

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x2,5+T - 25 A
230V - III		3x1,5+T - 16 A
400V - III+N		4x1,5+T - 10 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE7-05 R

Made of stainless steel.

Ribbed hot-plate.

Surface area: 20 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 4.5 kW.

Dimensions: 350 x 775 x 290 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	250	200	0		Prever Interruptor diferencial





700 Series

Fry-tops 700

ELECTRIC FRY-TOP, FTE/C7-05 L

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	835,00
Height	mm	290,00	585,00
Weigth	Kg	43,00	55,00
Volumen	m3	0,08	0,19

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x2,5+T - 25 A
230V - III		3x1,5+T - 16 A
400V - III+N		4x1,5+T - 10 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE/C7-05 L

Made of stainless steel.

Smooth hot-plate.

Surface area: 20 dm².

50 microns thickness chromium coated steel sheeting hot-plate.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 4.5 kW.

Dimensions: 350 x 775 x 290 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	250	200	0		Prever Interruptor diferencial





700 Series

Fry-tops 700

ELECTRIC FRY-TOP, FTE7-05 L

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	835,00
Height	mm	290,00	585,00
Weigth	Kg	43,00	55,00
Volumen	m3	0,08	0,19

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x2,5+T - 25 A
230V - III		3x1,5+T - 16 A
400V - III+N		4x1,5+T - 10 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE7-05 L

Made of stainless steel.

Smooth hot-plate.

Surface area: 20 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 4.5 kW.

Dimensions: 350 x 775 x 290 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	250	200	0		Prever Interruptor diferencial





700 Series

Fry-tops 700

ELECTRIC FRY-TOP, FTE7-10 R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	840,00
Height	mm	290,00	590,00
Weigth	Kg	70,00	81,00
Volumen	m3	0,16	0,37

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x10+T - 50 A
230V - III		3x4+T - 32 A
400V - III+N		4x1,5+T - 16 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE7-10 R

Made of stainless steel.

Ribbed hot-plate.

Surface area: 40 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 9 kW.

Dimensions: 700 x 775 x 290 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	600	200	0		Prever Interruptor diferencial





700 Series

Fry-tops 700

ELECTRIC FRY-TOP, FTE7-10 L+R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	840,00
Height	mm	290,00	590,00
Weigth	Kg	70,00	81,00
Volumen	m3	0,16	0,37

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x10+T - 50 A
230V - III		3x4+T - 32 A
400V - III+N		4x1,5+T - 16 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE7-10 L+R

Made of stainless steel.

½ smooth – ½ ribbed hot-plate.

Surface area: 40 dm².

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 9 kW.

Dimensions: 700 x 775 x 290 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	600	200	0		Prever Interruptor diferencial





700 Series

Fry-tops 700

ELECTRIC FRY-TOP, FTE/C7-10 L

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	840,00
Height	mm	290,00	590,00
Weigth	Kg	70,00	81,00
Volumen	m3	0,16	0,37

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x10+T - 50 A
230V - III		3x4+T - 32 A
400V - III+N		4x1,5+T - 16 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE/C7-10 L

Made of stainless steel.

Smooth hot-plate.

Surface area: 40 dm2.

50 microns thickness chromium coated steel sheeting hot-plate.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 9 kW.

Dimensions: 700 x 775 x 290 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	600	200	0		Prever Interruptor diferencial





700 Series

Fry-tops 700

GAS FRY-TOP, FTG7-10 V L+R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	840,00
Height	mm	290,00	590,00
Weigth	Kg	72,00	85,00
Volumen	m3	0,16	0,37

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	12,60
	Kcal/h	10.836,00
LPG	Consumption (kg/h)	1,05
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,33
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG7-10 V L+R

Made of stainless steel.

1/2 smooth + 1/2 ribbed hot-plate.

Surface area: 40 dm2.

2 tubular burners in stainless steel with pilot.

Safety valves and thermocouples.

Fat collector under the grill.

Power: 2x6.3 kW.


Total power: 12.6 kW.

Dimensions: 700 x 775 x 290 mm.

Certificate EQNET- CE

99AR307

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	57	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fry-tops 700

GAS FRY-TOP, FTG7-10 VL

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	840,00
Height	mm	290,00	590,00
Weigth	Kg	72,00	85,00
Volumen	m3	0,16	0,37

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	12,60
	Kcal/h	10.836,00
LPG	Consumption (kg/h)	1,05
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,33
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG7-10 VL

Made of stainless steel.

Smooth hot-plate.

Surface area: 40 dm2.

2 tubular burners in stainless steel with pilot.

Safety valves and thermocouples.

Fat collector under the grill.

Power: 2x6.3 kW.


Total power: 12.6 kW.

Dimensions: 700 x 775 x 290 mm.

Certificate EQNET- CE

99AR307

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	57	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fry-tops 700

GAS FRY-TOP, FTG7-10 VR

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	840,00
Height	mm	290,00	590,00
Weigth	Kg	72,00	85,00
Volumen	m3	0,16	0,37

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	12,60
	Kcal/h	10.836,00
LPG	Consumption (kg/h)	1,05
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,33
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG7-10 VR

Made of stainless steel.

Ribbed hot-plate.

Surface area: 40 dm2.

2 tubular burners in stainless steel with pilot.

Safety valves and thermocouples.

Fat collector under the grill.

Power: 2x6.3 kW.


Total power: 12.6 kW.

Dimensions: 700 x 775 x 290 mm.

Certificate EQNET- CE

99AR307

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	57	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fry-tops 700

GAS FRY-TOP, FTG7-10 L

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	840,00
Height	mm	290,00	590,00
Weigth	Kg	72,00	85,00
Volumen	m3	0,16	0,37

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	12,60
	Kcal/h	10.836,00
LPG	Consumption (kg/h)	1,05
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,33
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG7-10 L

Made of stainless steel.

Smooth hot-plate.

Surface area: 40 dm2.

2 tubular burners in stainless steel with pilot.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 2x6.3 kW.


Total power: 12.6 kW.

Dimensions: 700 x 775 x 290 mm.

Certificate EQNET- CE

99AR307

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	57	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fry-tops 700

GAS FRY-TOP, FTG7-10 L+R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	840,00
Height	mm	290,00	590,00
Weigth	Kg	72,00	85,00
Volumen	m3	0,16	0,37

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	12,60
	Kcal/h	10.836,00
LPG	Consumption (kg/h)	1,05
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,33
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG7-10 L+R

Made of stainless steel.

1/2 smooth + 1/2 ribbed hot-plate.

Surface area: 40 dm2.

2 tubular burners in stainless steel with pilot.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 2x6.3 kW.


Total power: 12.6 kW.

Dimensions: 700 x 775 x 290 mm.

Certificate EQNET- CE

99AR307

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	57	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fry-tops 700

GAS FRY-TOP, FTG7-10 R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	840,00
Height	mm	290,00	590,00
Weigth	Kg	72,00	85,00
Volumen	m3	0,16	0,37

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	12,60
	Kcal/h	10.836,00
LPG	Consumption (kg/h)	1,05
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,33
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG7-10 R

Made of stainless steel.

Ribbed hot-plate.

Surface area: 40 dm2.

2 tubular burners in stainless steel with pilot.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 2x6.3 kW.


Total power: 12.6 kW.

Dimensions: 700 x 775 x 290 mm.

Certificate EQNET- CE

99AR307

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	57	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fry-tops 700

GAS FRY-TOP, FTG/C7-10 L

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	840,00
Height	mm	290,00	590,00
Weigth	Kg	72,00	85,00
Volumen	m3	0,16	0,37

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	12,60
	Kcal/h	10.836,00
LPG	Consumption (kg/h)	1,05
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,33
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG/C7-10 L

Made of stainless steel.

Smooth hot-plate.

50 microns thickness chromium coated steel sheeting hot-plate.

Surface area: 40 dm2.

2 tubular burners in stainless steel with pilot.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 2x6.3 kW.


Total power: 12.6 kW.

Dimensions: 700 x 775 x 290 mm.

Certificate EQNET- CE

99AR307

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	57	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Fry-tops 700

ELECTRIC FRY-TOP, FTE7-10 L

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	840,00
Height	mm	290,00	590,00
Weigth	Kg	70,00	81,00
Volumen	m3	0,16	0,37

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x10+T - 50 A
230V - III		3x4+T - 32 A
400V - III+N		4x1,5+T - 16 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE7-10 L

Made of stainless steel.

Smooth hot-plate.

Surface area: 40 dm2.

Shielded elements in stainless steel for heating.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 9 kW.

Dimensions: 700 x 775 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	600	200	0		Prever Interruptor diferencial

