



700 Series

Ranges 700

ELECTRIC RANGE, CE7-20

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	840,00
Height	mm	290,00	530,00
Weigth	Kg	35,00	43,00
Volumen	m3	0,08	0,17

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		5,20 2x4+T - 32 A
230V - III		3x2,5+T - 25 A
400V - III+N		4x1,5+T - 16 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC RANGE, CE7-20

Made of stainless steel.

Cast iron hot- plates with shielded elements.


6 settings switch. Indicator lights.

Plates: 2 x 2600 W (Ø 220 mm).

Total power: 5.2 kW.

Dimensions: 350 x 775 x 290 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	321	335	0		Prever Interruptor diferencial





700 Series

Ranges 700

GAS RANGE, CG7-20

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	840,00
Height	mm	290,00	530,00
Weigth	Kg	35,00	43,00
Volumen	m3	0,08	0,17

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	10,50
	Kcal/h	9.030,00
LPG	Consumption (kg/h)	0,66
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,83
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-20

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 2 x 5.25 kW

Dimensions of the grid: 347x310 mm.

Fat collector under the grids.


Total power: 10.5 kW

Dimensions: 350 x 775 x 290 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	310	494	0	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-20 H

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	840,00
Height	mm	290,00	515,00
Weigth	Kg	35,00	43,00
Volumen	m3	0,08	0,17

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power		KW	13,80
		Kcal/h	11.868,00
LPG		Consumption (kg/h)	1,48
		Pressure (g/cm2)	37,00
Natural Gas		Consumption (m3/h)	1,90
		Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-20 H

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 2 x 6.9 kW

Dimensions of the grill: 347x310 mm.

Fat collector under the grids.


Total power: 13.8 kW.

Dimensions: 350 x 775 x 290 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
GAS	310	494	0	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-40 H

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	845,00
Height	mm	290,00	515,00
Weigth	Kg	61,00	75,00
Volumen	m3	0,16	0,32

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	27,60
	Kcal/h	23.736,00
LPG	Consumption (kg/h)	3,00
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	3,85
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-40 H

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 4 x 6.9 kW

Dimensions of the grill: 347x310 mm.

Fat collector under the grids.


Total power: 27.6 kW.

Dimensions: 700 x 775 x 290 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	0	R.3/4"G	Prever regulador y llave de corte individual



700 Series

Ranges 700

GAS RANGE, CG7-40



DIMENSIONS

		Article	Packed
Length	mm	700,00	740,00
Depth	mm	775,00	845,00
Height	mm	290,00	515,00
Weigth	Kg	61,00	75,00
Volumen	m3	0,16	0,32

ELECTRICITY

Not used			0,00
----------	--	--	------

WATER

Not used

GAS

Power		KW	22,65
		Kcal/h	19.479,00
LPG		Consumption (kg/h)	1,56
		Pressure (g/cm2)	37,00
Natural Gas		Consumption (m3/h)	2,09
		Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-40

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 1x6.9 + 3x5.25 kW

Dimensions of the grill: 347x310 mm.

Fat collector under the grids.


Total power: 22.65 kW.

Dimensions: 700 x 775 x 290 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	0	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

ELECTRIC RANGE, CE7-40

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	845,00
Height	mm	290,00	515,00
Weigth	Kg	63,00	75,00
Volumen	m3	0,16	0,32

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x10+T - 50 A
230V - III		3x4+T - 40 A
400V - III+N		4x2,5+T - 32 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC RANGE, CE7-40

Made of stainless steel.

Cast iron hot- plates with shielded elements.


6 settings switch. Indicator lights.

Plates: 3 x 2.600 W (Ø 220 mm) + 1 x 1.500 W (Ø 150 mm).

Total power: 9.3 kW.

Dimensions: 700 x 775 x 290 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	671	335	0		Prever Interruptor diferencial





700 Series

Ranges 700

ELECTRIC RANGE, CE7-20 Q

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	350,00	390,00
Depth	mm	775,00	840,00
Height	mm	290,00	530,00
Weigth	Kg	35,00	43,00
Volumen	m3	0,08	0,17

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x4+T - 32 A
230V - III		3x2,5+T - 25 A
400V - III+N		4x1,5+T - 16 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC RANGE, CE7-20 Q

Made of stainless steel.

Cast iron square hot- plates with shielded elements.


6 settings switch. Indicator lights.

Plates: 2 x 3,000 W (300 x 300 mm).

Total power: 6 KW.

Dimensions: 350 x 775 x 290 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	321	335	0		Prever Interruptor diferencial





700 Series

Ranges 700

ELECTRIC RANGE, CE7-40 Q

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	845,00
Height	mm	290,00	515,00
Weigth	Kg	63,00	75,00
Volumen	m3	0,16	0,32

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x10+T - 50 A
230V - III		3x4+T - 40 A
400V - III+N		4x2,5+T - 32 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC RANGE, CE7-40 Q

Made of stainless steel.

Cast iron hot- plates with shielded elements.


6 settings switch. Indicator lights.

Square plates: 4 x 3.000 W (300 x 300).

Total power: 12 kW.

Dimensions: 700 x 775 x 290 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	671	335	0		Prever Interruptor diferencial





700 Series

Ranges 700

ELECTRIC RANGE, CE7-41

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	745,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	130,00	152,00
Volumen	m3	0,46	0,66

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		15,30
230V - III		2x16+T - 80 A
400V - III+N		3x10+T - 63 A
		4x4+T - 40 A

WATER

Not used

GAS

Not used

STEAM

Not used


AIR

Not used

ELECTRIC RANGE, CE7-41

Made of stainless steel.
 Cast iron hot- plates with shielded elements.
 6 settings switch. Indicator lights.
 Plates: 3 x 2.600 W (Ø 220 mm) + 1 x 1.500 W (Ø 150 mm).
 2/1 GN oven made of stainless steel, with upper and lower heating elements (3 + 3 KW).
 Selector switch for the elements.
 Thermostatic control (130 °C – 350 °C).
 Oven power: 6 kW.
 Total power : 15.3 kW.
 Dimensions: 700 x 775 x 850 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	32	515	150		Prever Interruptor diferencial





700 Series

Ranges 700

GAS RANGE, CG7-51

DIMENSIONS

		Article	Packed
Length	mm	1.050,00	860,00
Depth	mm	775,00	1.090,00
Height	mm	850,00	1.040,00
Weigth	Kg	160,00	202,00
Volumen	m3	0,69	0,97

ELECTRICITY

Not used			0,00
----------	--	--	------

WATER

Not used

GAS

Power		KW	37,35
		Kcal/h	32.121,00
LPG		Consumption (kg/h)	3,10
		Pressure (g/cm2)	37,00
Natural Gas		Consumption (m3/h)	3,93
		Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-51

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition. Cast iron gratings and burners.

Burners: 2x6.9 + 2x5.25 kW

Dimensions of the grill: 347x310 mm.

One solid top on the center of the work-top, cast iron burner.

Burner of 5.25 kW.

Solid top dimensions: 347x620 mm.

2/1 GN oven made of stainless steel with tubular burner in stainless steel.

Pilot and thermocouple.

Thermostatic control (130 °C - 350 °C).

Oven burner: 7.8 kW.

Auxiliary neutral cabinet.


Total power: 37.35 kW.

Dimensions: 1050 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	1.010	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-61

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	1.050,00	1.090,00
Depth	mm	775,00	855,00
Height	mm	850,00	1.090,00
Weigth	Kg	155,00	196,50
Volumen	m3	0,69	1,02

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power		KW	42,60
		Kcal/h	36.636,00
LPG	Consumption (kg/h)		3,10
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		3,93
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-61

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition. Cast iron gratings and burners.

Burners: 2x6.9 + 4x5.25 kW

Dimensions of the grill: 347x310 mm.

Fat collector under the grids.

2/1 GN oven made of stainless steel, with tubular burner in stainless steel.

Pilot and thermocouple.

Thermostatic control (130 °C - 350 °C).

Oven burner: 7.8 kW.

Auxiliary neutral cabinet.


Total power: 42.6 kW.

Dimensions: 1050 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	1.010	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-61 H

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	1.050,00	1.090,00
Depth	mm	775,00	855,00
Height	mm	850,00	1.090,00
Weigth	Kg	155,00	196,50
Volumen	m3	0,69	1,02

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	49,20
	Kcal/h	42.312,00
LPG	Consumption (kg/h)	4,30
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	5,50
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-61 H

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 6x6.9 kW

Dimensions of the grill: 347x310 mm.

Fat collector under the grids.

2/1 GN oven made of stainless steel, with tubular burner in stainless steel.

Pilot and thermocouple.

Thermostatic control (130 °C - 350 °C).

Oven burner: 7.8 kW.

Auxiliary neutral cabinet.


Total power: 49.2 kW.

Dimensions: 1050 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	1.010	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-11

DIMENSIONS

		Article	Packed
Length	mm	700,00	740,00
Depth	mm	775,00	840,00
Height	mm	850,00	1.055,00
Weigth	Kg	165,00	185,50
Volumen	m3	0,46	0,66

ELECTRICITY

Not used			0,00
----------	--	--	------

WATER

Not used

GAS

Power		KW	16,20
		Kcal/h	13.932,00
LPG		Consumption (kg/h)	1,24
		Pressure (g/cm2)	37,00
Natural Gas		Consumption (m3/h)	1,58
		Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-11

Made of stainless steel.

Solid top on the work-top.

Cast iron burner under the solid top.

Dimensions of the solid top plate: 695 x 620 mm.

Burner power: 8.4 kW.

2/1 GN oven made of stainless steel, with tubular burner in stainless steel.

Pilot and thermocouple.

Thermostatic control (130 °C - 350 °C).

Oven burner: 7.8 kW.


Total power: 16.2 kW.

Dimensions: 700 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-31 D

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.080,00
Weigth	Kg	129,00	147,00
Volumen	m3	0,46	0,67

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power		KW	25,20
		Kcal/h	21.672,00
LPG	Consumption (kg/h)		2,19
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		2,78
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-31 D

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition. Cast iron gratings and burners.

Burners: 1x6.9 + 1x5.25 kW

Dimensions of the grill: 347x310 mm.

One solid top on the right side of the work-top, cast iron burner.

Burner of 5.25 kW.

Solid top dimensions: 347x620 mm.

2/1 GN oven made of stainless steel with tubular burner in stainless steel.

Pilot and thermocouple.

Thermostatic control (130 °C - 350 °C).

Oven burner: 7,8 kW.


Total power: 25.2 kW.

Dimensions: 700 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-31 I

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.080,00
Weigth	Kg	129,00	147,00
Volumen	m3	0,46	0,67

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power		KW	25,20
		Kcal/h	21.672,00
LPG		Consumption (kg/h)	2,19
		Pressure (g/cm2)	37,00
Natural Gas		Consumption (m3/h)	2,78
		Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-31 I

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition. Cast iron gratings and burners.

Burners: 1x6.9 + 1x5.25 kW

Dimensions of the grill: 347x310 mm.

One solid top on the left side of the work-top, cast iron burner.

Burner of 5.25 kW.

Solid top dimensions: 347x620 mm.

2/1 GN oven made of stainless steel with tubular burner in stainless steel.

Pilot and thermocouple.

Thermostatic control (130 °C - 350 °C).

Oven burner: 7.8 kW.


Total power: 25.2 kW.

Dimensions: 700 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-41

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	745,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	134,00	152,00
Volumen	m3	0,46	0,66

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power		KW	30,45
		Kcal/h	26.187,00
LPG	Consumption (kg/h)		2,19
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		2,78
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-41

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 1x6.9 + 3x5.25 kW

Dimensions of the grill: 347x310 mm.

Fat collector under the grids.

2/1 GN oven made of stainless steel, with tubular burner in stainless steel.

Pilot and thermocouple.

Thermostatic control (130 °C – 350 °C).

Oven burner: 7.8 kW.


Total power: 30.45 kW.

Dimensions: 700 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-41 H

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	745,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	134,00	152,00
Volumen	m3	0,46	0,66

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	35,40
	Kcal/h	30.444,00
LPG	Consumption (kg/h)	3,15
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	4,23
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-41 H

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 4x6.9 kW

Dimensions of the grill: 347x310 mm.

Fat collector under the grids.

2/1 GN oven made of stainless steel, with tubular burner in stainless steel.

Pilot and thermocouple.

Thermostatic control (130 °C - 350 °C).

Oven burner: 7.8 kW.


Total power: 35.4 kW.

Dimensions: 700 x 775 x 850 mm

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-10

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	745,00
Depth	mm	775,00	835,00
Height	mm	290,00	525,00
Weigth	Kg	90,00	109,00
Volumen	m3	0,16	0,33

GAS RANGE, CG7-10

Made of stainless steel.

Solid top on the work-top.

Cast iron burner under the solid top.

Dimensions of the solid top plate: 695 x 620 mm.

Total power: 8.4 kW.

Dimensions: 700 x 775 x 290 mm.

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	8,40
	Kcal/h	7.224,00
LPG	Consumption (kg/h)	0,70
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,89
	Pressure (g/cm2)	18,00

STEAM

Not used


AIR

Not used

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	0	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-30 I

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	740,00
Depth	mm	775,00	835,00
Height	mm	290,00	515,00
Weigth	Kg	61,00	75,00
Volumen	m3	0,16	0,32

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	17,40
	Kcal/h	14.964,00
LPG	Consumption (kg/h)	1,56
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	2,09
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-30 I

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition. Cast iron gratings and burners.

Burners: 1x6.9 + 1x5.25 kW

Dimensions of the grill: 347x310 mm.

One solid top on the left side of the work-top, cast iron burner.

Burner of 5.25 kW.

Solid top dimensions: 347x620 mm.


Total power: 17.4 kW.

Dimensions: 700 x 775 x 290 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	0	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-30 D

DIMENSIONS

		Article	Packed
Length	mm	700,00	740,00
Depth	mm	775,00	835,00
Height	mm	290,00	515,00
Weigth	Kg	61,00	75,00
Volumen	m3	0,16	0,32

ELECTRICITY

Not used			0,00
----------	--	--	------

WATER

Not used

GAS

Power	KW	17,40
	Kcal/h	14.964,00
LPG	Consumption (kg/h)	1,56
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	2,09
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-30 D

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition. Cast iron gratings and burners.

Burners: 1x6.9 + 1x5.25 kW

Dimensions of the grill: 347x310 mm.

One solid top on the right side of the work-top, cast iron burner.

Burner of 5.25 kW.

Solid top dimensions: 347x620 mm.


Total power: 17.4 kW.

Dimensions: 700 x 775 x 290 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	660	494	0	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-50

DIMENSIONS

		Article	Packed
Length	mm	1.050,00	1.200,00
Depth	mm	775,00	835,00
Height	mm	290,00	515,00
Weigth	Kg	100,00	115,00
Volumen	m3	0,24	0,50

ELECTRICITY

Not used			0,00
----------	--	--	------

WATER

Not used

GAS

Power		KW	29,55
		Kcal/h	25.413,00
LPG		Consumption (kg/h)	2,10
		Pressure (g/cm2)	37,00
Natural Gas		Consumption (m3/h)	2,80
		Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-50

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition. Cast iron gratings and burners.

Burners: 2x6.9 + 2x5.25 kW

Dimensions of the grill: 347x310 mm.

One solid top of 347x620 mm, cast iron burner.

Solid top burner of 5.25 kW.


Total power: 29.55 kW.

Dimensions: 1050 x 775 x 2900 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	1.010	494	0	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-60

DIMENSIONS

		Article	Packed
Length	mm	1.050,00	1.200,00
Depth	mm	775,00	845,00
Height	mm	290,00	515,00
Weigth	Kg	80,00	90,00
Volumen	m3	0,24	0,48

ELECTRICITY

Not used			0,00
----------	--	--	------

WATER

Not used

GAS

Power		KW	34,80
		Kcal/h	29.928,00
LPG		Consumption (kg/h)	2,10
		Pressure (g/cm2)	37,00
Natural Gas		Consumption (m3/h)	2,80
		Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-60

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 2x6.9 + 4x5.25 kW

Dimensions of the grill: 347x310 mm.

Fat collector under the grids.


Total power: 34.8 kW.

Dimensions: 1,050 x 775 x 290 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	1.010	494	0	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CG7-60 H

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	1.050,00	1.200,00
Depth	mm	775,00	845,00
Height	mm	290,00	515,00
Weigth	Kg	80,00	90,00
Volumen	m3	0,24	0,48

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	41,40
	Kcal/h	35.604,00
LPG	Consumption (kg/h)	3,50
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	4,50
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CG7-60 H

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 6x6.9 kW.

Dimensions of the grill: 347x310 mm.


Total power: 41.4 kW.

Dimensions: 1,050 x 775 x 290 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	1.010	494	0	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS AND ELECTRIC RANGE, CGE7-41

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	745,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	134,00	152,00
Volumen	m3	0,46	0,66

ELECTRICITY

<u>Electric power</u>		KW	
230V - I+N			2x4+T - 32 A
230V - III			3x2,5+T - 20 A
400V - III+N			4x1,5+T - 16 A

WATER

Not used

GAS

Power		KW	22,65
		Kcal/h	19.479,00
LPG	Consumption (kg/h)		1,56
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		2,09
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used


GAS AND ELECTRIC RANGE, CGE7-41

Made of stainless steel.
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 1x6.9 + 3x5.25 kW.
 Dimensions of the grid: 347x310 mm.
 2/1 GN oven made of stainless steel, with upper and lower heating elements.
 Selector switch for the elements.
 Thermostatic control (130 °C – 350 °C).
 Oven power: 6 kW - electric heating.
 Total gas power: 22.65 kW.
 Total electrical power: 6 kW.
 Dimensions: 700 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	32	515	150		Prever Interruptor diferencial
GAS	660	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS AND ELECTRIC RANGE, CGE7-41 H

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	745,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	134,00	152,00
Volumen	m3	0,46	0,66

ELECTRICITY

<u>Electric power</u>		KW	
230V - I+N			2x4+T - 32 A
230V - III			3x2,5+T - 20 A
400V - III+N			4x1,5+T - 16 A

WATER

Not used

GAS

Power		KW	27,60
		Kcal/h	23.736,00
LPG	Consumption (kg/h)		3,00
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		3,85
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used

GAS AND ELECTRIC RANGE, CGE7-41 H

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition. Cast iron gratings and burners.

Burners: 4x6.9 kW.

Dimensions of the grid: 347x310 mm.

2/1 GN oven made of stainless steel, with upper and lower heating elements.

Selector switch for the elements.

Thermostatic control (130 °C - 350 °C).

Oven power: 6 kW - electric heating.

Total gas power: 27.6 kW.


Total electrical power: 6 kW.

Dimensions: 700 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	32	515	150		Prever Interruptor diferencial
GAS	660	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

ELECTRIC RANGE, CE7-41 Q

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	700,00	745,00
Depth	mm	775,00	835,00
Height	mm	850,00	1.060,00
Weigth	Kg	130,00	152,00
Volumen	m3	0,46	0,66

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x16+T - 80 A
230V - III		3x10+T - 63 A
400V - III+N		4x4+T - 40 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC RANGE, CE7-41 Q

Made of stainless steel.

Cast iron hot- plates with shielded elements.

6 settings switch. Indicator lights.

Square plates: 4 x 3.000 W (300 x 300).

2/1 GN oven made of stainless steel, with upper and lower heating elements (3 + 3 KW).

Selector switch for the elements.


Thermostatic control (130 °C – 350 °C).

Oven power: 6 kW.

Total power : 18 KW.

Dimensions: 700 x 775 x 850 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	32	515	150		Prever Interruptor diferencial





700 Series

Ranges 700

GAS RANGE, CGB7-61 H

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	1.050,00	1.090,00
Depth	mm	775,00	855,00
Height	mm	850,00	1.090,00
Weigth	Kg	155,00	196,50
Volumen	m3	0,69	1,02

ELECTRICITY

Not used			0,00
----------	--	--	------

WATER

Not used

GAS

Power		KW	49,20
		Kcal/h	42.312,00
LPG		Consumption (kg/h)	4,30
		Pressure (g/cm2)	37,00
Natural Gas		Consumption (m3/h)	5,50
		Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CGB7-61 H

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 6x6.9 kW.

Dimensions of the grid: 347x310 mm.

UK style oven made of stainless steel, with temperature gradient from top to bottom of oven.

Pilot and thermocouple.

Thermostatic control (130 °C - 350 °C).

Double side door.

Oven burner: 7.8 kW.


Total power: 49.2 kW.

Dimensions: 1050 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	1.010	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CGB7-61

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	1.050,00	1.090,00
Depth	mm	775,00	855,00
Height	mm	850,00	1.090,00
Weigth	Kg	155,00	196,50
Volumen	m3	0,69	1,02

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	42,60
	Kcal/h	36.636,00
LPG	Consumption (kg/h)	3,10
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	3,93
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CGB7-61

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 2x6.9 + 4x5.25 kW.

Dimensions of the grid: 347x310 mm.

UK style oven made of stainless steel, with temperature gradient from top to bottom of oven.

Pilot and thermocouple.

Thermostatic control (130 °C – 350 °C).

Double side door.

Oven burner: 7.8 kW.


Total power: 42.6 kW.

Dimensions: 1050 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	1.010	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CGB7-61 RH

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	1.050,00	1.090,00
Depth	mm	775,00	860,00
Height	mm	850,00	1.040,00
Weigth	Kg	155,00	196,50
Volumen	m3	0,69	0,97

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	49,20
	Kcal/h	42.312,00
LPG	Consumption (kg/h)	4,30
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	5,50
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CGB7-61 RH

Model with castors.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 6x6.9 kW.

Dimensions of the grid: 347x310 mm.

UK style oven made of stainless steel, with temperature gradient from top to bottom of oven.

Pilot and thermocouple.

Thermostatic control (130 °C - 350 °C).

Double side door.

Oven burner: 7.8 kW.


Total power: 49.2 kW.

Dimensions: 1050 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	1.010	494	105	R.3/4"G	Prever regulador y llave de corte individual





700 Series

Ranges 700

GAS RANGE, CGB7-61 R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	1.050,00	1.090,00
Depth	mm	775,00	855,00
Height	mm	850,00	1.090,00
Weigth	Kg	155,00	196,50
Volumen	m3	0,69	1,02

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	42,60
	Kcal/h	36.636,00
LPG	Consumption (kg/h)	3,10
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	3,93
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS RANGE, CGB7-61 R

Model with castors.

Made of stainless steel.

Open hobs with safety valve and thermocouples.

Pilots for ignition.

Cast iron gratings and burners.

Burners: 2x6.9 + 4x5.25 kW.

Dimensions of the grid: 347x310 mm.

UK style oven made of stainless steel, with temperature gradient from top to bottom of oven.

Pilot and thermocouple.

Thermostatic control (130 °C - 350 °C).

Double side door.

Oven burner: 7.8 kW.

Total power: 42.6 kW.

Dimensions: 1050 x 775 x 850 mm.

Certificate EQNET- CE

Cgaz-1312BT5112

Connections points	X	Y	Z	Diameter	Information
GAS	1.010	494	105	R.3/4"G	Prever regulador y llave de corte individual

