Catalogue:

CATERING

Chapter:

OVENS

Article:

ACG-201 LPG 230V 1N 50Hz

Code:

19011234

DIMENSIONS AND WEIGHTS

		Net dimension	Packed
Length	mm	**1.045,00**	**1.015,00**
Depth	mm	**925,00**	**1.070,00**
Height	mm	**1.850,00**	**2.145,00**
Weight	kg	**286,00**	**316,00**
Volume	m3	**1,79**	**2,33**

ELECTRICITY	**230V**	**50Hz**	
	Power	**2,40**	kW
Connections	230 V. 1+N+T	**2X1,5+T - 10 A**	
	230 V. III+T		
	400 V. III+N+T		
GAS	Power	**36,00**	kW
	Gas type	**LPG**	
	Consumption	**3,81**	kg/h
	Pressure	**LPG G30/G31 28-30/37 mbar**	
WATER	Consumption	**30**	lit/h
	Pressure	**Water Pres:200-400kPa(2-4bar)**	
STEAM	Not necessary		
AIR	Not necessary		

REFRIGERATION

LEVEL SOUND **62,00** db

CERTIFICATES

Connections and diameters	
ELECTRICITY	**YES**
DRAIN	1"
SOFT WATER	3/4"
COLD WATER	3/4"
GAS	R.3/4"G

DESCRIPTION

ADVANCE CONCEPT INJECTION COMBI OVEN, ACG-201

Technology made simple:

- Easy to use
- Efficient
- Simple
- Perfect results

Capacity for 20 1/1-GN trays.

Stainless steel burner with electronic control system with sparking plug ignition.

Frequency modulation for the convection burner.
Digital push-button controls and two “Scroll” buttons.
5 Cooking methods: Steam, Combi, Regeneration, Delta and Convection (up to 300ºC).
Steam generated by injection in the cooking chamber.
Electronic temperature core probe.
Preheating option.
3 Speeds - 2 power ranges.
Cold-Down chamber cooling system.
“Auto-reverse” system to reverse fan rotation.
Error detection system.
Door with double glass.
“Repair service” mode system.
IPX5 Protection.
AUTOMATIC CLEANING - Wash program for the cooking chamber.

Electrical connection: 230 V - 1+N - 2.4 KW.

Gas heating capacity: 36 kW.
Dimensions: 929 x 964 x 1.841 mm.

Accessories in option:

- External shower