



Refrigeration

Blast chillers & freezers

BLAST CHILLER & FREEZER, ATM-081

143317000000

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	790,00	800,00
Depth	mm	800,00	900,00
Height	mm	1.290,00	1.500,00
Weight	Kg	145,00	150,00
Volume	m3	0,82	1,23

ELECTRICITY

<u>Electric power</u>	KW	
Voltage 230V - 1+N		2x2,5+T - 12 A
Voltage 230V - III		
Voltage 400V - III+N		4x1,5 +T - 12 A

PLUMBING - WATER

GAS

Not used

STEAM

Not used

AIR

Not used

REFRIGERATION

R-404

Certification EQNET- CE

SGS-2103-0906-1

BLAST CHILLER & FREEZER, ATM-081

Made of stainless steel .

Adjustable legs in stainless steel .

Sliding guides for Gastronorm trays and Euronorm trays (60x40 cm).

Doors with automatic locking device.

Blast chiller / freezer models designed to reduce the temperature from +70°C to +3°C (chilling) or from +20°C to -18°C (freezing).

A choice of hard or soft chilling programmes.

Can be made two chilling cycles and two freezing cycles.

Duration of the cycles:

- Chilling: 90 minutes.

- Freezing: 270 minutes (3 hours).

Electronic timer and temperature probe standard on all models.

Probe controlled or time controlled blast chilling options.

Automatic end-of cycle alarm or hold which maintains chill temperature after blast chilling cycle is complete.

Removable, ventilated airtight compressor.

R-404 A cooler, no CFC.

60 mm thick injected polyurethane insulation,

40 kg/m3 density. No CFC.

Copper evaporator with aluminium fins.

Forced draught.

Automatic evaporation of water during defrosting.

Capacity: 8 levels 1/1 GN or 60x40 cm.

Distance between levels: 65 mm.

Production: 25 Kg/Cycle (chilling) or 16 Kg/Cycle (freezing).


Operating voltage: 230 V - 1+N - 50 / 60 Hz.

Consumption: 2,000 W.

Refrigeration power: 1,300 W.

Dimensions: 790 x 800 x 1,290 mm.

<u>Connections</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	730	0	110		Prever Interruptor diferencial
DRAIN	580	215	110		



MODELO / MODEL		ATM-081	
Dimensiones Exteriores	mm	790x800x1290	
External Dimensions			
Dimensiones Interiores	mm	670x410x645	
Internal Dimensions			
Tipo Abatidor		Mixto	
Type Blast Chiller			
Capacidad GN	nº	8 GN1/1	
Capacity GN			
Capacidad EN	nº	8 EN	
Capacity EN			
Separacion entre bandejas	mm	65	
Interstep trays			
Espesor aislamiento	mm	60	
Thickness			
Medidas hueco puerta	mm	670x630	
door opening measures			
Refrigerante	Gas	R404A	
Refrigerant			
Ciclo refrigeración	°C	+90/+3	
Chilling cycle			
Ciclo Congelación	°C	+90/-18	
Freezing cycle			
Capacidad Abatimiento	90'	Kg	25
Chilling capacity			
Capacidad Congelación	240'	Kg	16
Freezing capacity			
Grupo frigorífico	°C	Incorporado	
Refrigeration Unit			
Alimentación eléctrica	V/~ /Hz	230/1/50	
Electric Power supply			
Intensidad Máxima	A	9,5	
Max. Absorbed current			
Potencia Frigorífica	W	1300	
Capacity refrigeration			
Potencia eléctrica	W	2000	
Input electric Power			
Forma entrada bandeja	mm	530	
Input tray			
Volumen bruto exterior	m ³	1,23	
Total Volume external			
Volumen interior neto	m ³	0,173	
Net Volume internal			
Peso	Kg	145	
Weigh			

