



Refrigeration

Blast chillers & freezers

BLAST CHILLER & FREEZER, ATM-102

143325000000

DIMENSIONS

		Article	Packed
Length	mm	1.270,00	1.300,00
Depth	mm	1.090,00	1.100,00
Height	mm	1.800,00	2.000,00
Weight	Kg	270,00	280,00
Volume	m3	2,49	3,25

ELECTRICITY

Electric power	KW	
Voltage 230V -1+N		2,30
Voltage 230V - III		
Voltage 400V - III+N		4x2,5 +T -12A

PLUMBING - WATER

GAS

Not used

STEAM

Not used

AIR

Not used

REFRIGERATION

R-404

Certification EQNET- CE

SGS-2103-0906-1

BLAST CHILLER & FREEZER, ATM-102

Made of stainless steel .

Adjustable legs in stainless steel .

Sliding guides for Gastronorm trays and Euronorm trays (60x40 cm).

Doors with automatic locking device.

Blast chiller / freezer models designed to reduce the temperature from +70°C to +3°C (chilling) or from +20°C to -18°C (freezing).

A choice of hard or soft chilling programmes.

Can be made two chilling cycles and two freezing cycles.

Duration of the cycles:

- Chilling: 90 minutes.

- Freezing: 270 minutes (3 hours).

Electronic timer and temperature probe standard on all models.

Probe controlled or time controlled blast chilling options.

Automatic end-of cycle alarm or hold which maintains chill temperature after blast chilling cycle is complete.

Removable, ventilated airtight compressor.

R-404 A cooler, no CFC.

60 mm thick injected polyurethane insulation,

40 kg/m3 density. No CFC.

Copper evaporator with aluminium fins.

Forced draught.

Automatic evaporation of water during defrosting.

Capacity: 20 levels GN-1/1 or 10 levels 2/1 GN or 60x40 cm.

Distance between levels: 70 mm.


Production: 70 Kg/Cycle (chilling) or 50 Kg/Cycle (freezing).

Operating voltage: 400 V - 3+N - 50 / 60 Hz. - 2,300 W.

Refrigeration power: 2,850 W.

Dimensions: 1.270 x 1.090 x 1.800 mm.

Connections	X	Y	Z	Diameter	Information
ELECTRICITY	1.065	0	130		Prever Interruptor diferencial
DRAIN	390	190	130		



MODELO / MODEL		ATM-102
Dimensiones Exteriores External Dimensions	mm	1270x1090x1800
Dimensiones Interiores Internal Dimensions	mm	654x970x815
Tipo Abatidor Type Blast Chiller		Mixto
Capacidad GN Capacity GN	nº	10 GN2/1
Capacidad EN Capacity EN	nº	10 EN
Separacion entre bandejas Interstep trays	mm	70
Espesor aislamiento Thickness	mm	100-60
Medidas hueco puerta door opening measures	mm	654x790
Refrigerante Refrigerant	Gas	R404A
Ciclo refrigeración Chilling cycle	°C	+90/+3
Ciclo Congelación Freezing cycle	°C	+90/-18
Capacidad Abatimiento Chilling capacity	90'	Kg 70
Capacidad Congelación Freezing capacity	240'	Kg 50
Grupo frigorífico Refrigeration Unit	°C	Incorporado
Alimentación eléctrica Electric Power supply	V/~ /Hz	400/3/50
Intensidad Máxima Max. Absorbed current	A	6,9
Potencia Frigorífica Capacity refrigeration	W	2850
Potencia eléctrica Input electric Power	W	2300
Forma entrada bandeja Input tray	mm	530
Volumen bruto exterior Total Volume external	m ³	3,25
Volumen interior neto Net Volume internal	m ³	0,45
Peso Weigh	Kg	280

