



Refrigeration

Blast chillers & freezers

BLAST CHILLER & FREEZER, ATM-161

143323000000

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	790,00	800,00
Depth	mm	800,00	900,00
Height	mm	1.950,00	2.200,00
Weight	Kg	200,00	220,00
Volume	m3	1,23	1,79

ELECTRICITY

<u>Electric power</u>		KW	
Voltage 230V -1+N			3,50
Voltage 230V - III			
Voltage 400V - III+N		4x1,5 +T - 12 A	

PLUMBING - WATER

GAS

Not used

STEAM

Not used

AIR

Not used

REFRIGERATION

R-404


Certification EQNET- CE

SGS-2103-0906-1

BLAST CHILLER & FREEZER, ATM-161

Made of stainless steel .
Adjustable legs in stainless steel .
Sliding guides for Gastronorm trays and Euronorm trays (60x40 cm).
Doors with automatic locking device.
Blast chiller / freezer models designed to reduce the temperature from +70°C to +3°C (chilling) or from +20°C to -18°C (freezing).
A choice of hard or soft chilling programmes.
Can be made two chilling cycles and two freezing cycles.
Duration of the cycles:
- Chilling: 90 minutes.
- Freezing: 270 minutes (3 hours).
Electronic timer and temperature probe standard on all models.
Probe controlled or time controlled blast chilling options.
Automatic end-of cycle alarm or hold which maintains chill temperature after blast chilling cycle is complete.
Removable, ventilated airtight compressor.
R-404 A cooler, no CFC.
60 mm thick injected polyurethane insulation, 40 kg/m3 density. No CFC.
Copper evaporator with aluminium fins.
Forced draught.
Automatic evaporation of water during defrosting.
Capacity: 16 levels 1/1 GN or 60x40 cm.
Distance between levels: 65 mm.
Production: 40 Kg/Cycle (chilling) or 28 Kg/Cycle (freezing).
Operating voltage: 400 V. 3+N+E - 50 / 60 Hz.
Consumption: 3,500 W.
Refrigeration power: 2,850 W.
Dimensions: 790 x 800 x 1,950 mm.

<u>Connections</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	730	0	110		Prever Interruptor diferencial
DRAIN	580	215	110		



MODELO / MODEL		ATM-161
Dimensiones Exteriores External Dimensions	mm	790x800x1950
Dimensiones Interiores Internal Dimensions	mm	670x410x1165
Tipo Abatidor Type Blast Chiller		Mixto
Capacidad GN Capacity GN	nº	16 GN1/1
Capacidad EN Capacity EN	nº	16 EN
Separacion entre bandejas Interstep trays	mm	65
Espesor aislamiento Thickness	mm	60
Medidas hueco puerta door opening measures	mm	670x1150
Refrigerante Refrigerant	Gas	R404A
Ciclo refrigeración Chilling cycle	°C	+90/+3
Ciclo Congelación Freezing cycle	°C	+90/-18
Capacidad Abatimiento Chilling capacity	90'	Kg 40
Capacidad Congelación Freezing capacity	240'	Kg 28
Grupo frigorífico Refrigeration Unit	°C	Incorporado
Alimentación eléctrica Electric Power supply	V/~ /Hz	400/3/50
Intensidad Máxima Max. Absorbed current	A	6,2
Potencia Frigorífica Capacity refrigeration	W	2850
Potencia eléctrica Input electric Power	W	3500
Forma entrada bandeja Input tray	mm	530
Volumen bruto exterior Total Volume external	m ³	1,79
Volumen interior neto Net Volume internal	m ³	0,32
Peso Weigh	Kg	200

