Refrigeration

NEO Concept Pizza and salad refrigerated counters

PIZZA AND SALAD REFRIGERATED TABLE, CMPZ1-135

DIMENSIONS		Article	Packed
Length	mm	**1.350,00**	**1.350,00**
Depth	mm	**700,00**	**700,00**
Height	mm	**1.050,00**	**1.050,00**
Weigth	Kg	**105,00**	**115,00**
Volumen	m3	**0,99**	**0,99**

ELECTRICITY

Electric power	KW	**0,37**
230V -1+N		**2x1,5+T - 2 A**
230V - III		
400V - III+N		

WATER

Not used

GAS

Not used

STEAM Not used

AIR Not used

REFRIGERATION R-134 a

Certificate EQNET- CE **SGS-2103-0906-1**

PIZZA AND SALAD REFRIGERATED TABLE, CMPZ1-135
Stainless steel exterior, except rear panel.
Stainless steel interior, with rounded corners at the bottom.
Stainless steel adjustable legs, .
Equipped with 1 pair of guides 1/1 GN per door.
Rotating door-type grid panel.
Working temperature -2ºC, +8ºC at room temperature of 38ºC.
Removable, ventilated airtight compressor.
R-134 A coolant.
50-mm thick injected polyurethane insulation. Density 40 kg.
No CFC.
Copper evaporator with aluminium fins.
Automatic evaporation of water during defrosting.
Illuminated general switch.
Electronic temperature and defrosting control and display.
Doors with automatic locking device and fixed opening.
Refrigerated ingredient unit with 7 housing for 1/4 GN containers
Containers not included.
Operating voltage 220/240 V - I - 50/60 Hz.
N. of doors: 2.
Capacity (litres): 290.
Refrigeration power: 250 W.
Dimensions: 1,350 x 700 x 1,050 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	214	5	310		Prever Interruptor diferencial