



**Dishwashing**

**EVO Generation - Concept**

**DISHWASHER CO-110 DD**

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	<b>658,00</b>	<b>700,00</b>
Depth	mm	<b>756,00</b>	<b>840,00</b>
Height	mm	<b>1.554,00</b>	<b>2.040,00</b>
Weight	Kg	<b>145,00</b>	<b>166,00</b>
Volume	m3		<b>1,20</b>

<u>ELECTRICITY</u>			
<u>Electric power</u>		KW	<b>11,10</b>
Voltage 230V - I+N			<b>2x16+T - 63 A</b>
Voltage 230V - III			<b>3x6+T - 40 A</b>
Voltage 400V - III+N			<b>4x2,5+T - 25 A</b>

<u>WATER</u>			
Water consumption (lit/h)			<b>108,00</b>
Pressure (Kg/cm2)			<b>2 ÷ 4</b>

GAS  
Not used

STEAM  
Not used

AIR  
Not used

<u>LEVEL SOUND</u>	(dB)	<b>63,00</b>
--------------------	------	--------------

**DISHWASHER CO-110 DD**

Hood type dishwasher - EVO Generation - Concept range.  
Hourly production: 40 baskets/hour - 720 dishes/hour.  
Clearance (max ware height): 440 mm.  
Wash cycles: 90"- 180".

Made of stainless steel.  
Counterbalanced hood.  
Double rotating wash and rinse systems, made of AISI-304 stainless steel.  
One wash pump, 600 W.  
Tank with 4.5 kW heating power.  
Tank capacity: 34 litres.  
Boiler heating power: 6 kW.  
Boiler capacity: 9 litres.  
Water consumption: 2.4 litres/rinse.  
Thermostatic temperature control: washing at 60°C and rinsing at 90°C.  
Safety thermostats.  
Built-in automatic rinse dispenser and detergent doser.  
Built-in non-return valve.  
Safety magnetic switch for hood opening.  
Adjustable legs.  
Water protection rating: IPX4  
Total power: 6,60 / 11,1 kW.  
Dimensions: 658 x 756 x 1540 mm.

Baskets equipment: 1 x CT-10, 1 x CP-16/18 and 2 cutlery containers.

<u>Connections</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	210	50	65		
DRAIN	370	50	65	30 x 25	
SOFT COLD WATER	305	50	65	3/4"	

